



← 1.60±0.30  
 ← 0.70 TOP GLASS (ITO FACE DOWN)  
 ← 0.20 OCA  
 ← 0.70 BOTTOM GLASS (ITO FACE UP)

4.80 MAX Components height

J2(USB) PIN TABLE

PIN#	J2 (USB)
1	5.0V
2	D-
3	D+
4	GND

NOTES:

1. ALL UNITS IN MM.
2. OPERATING TEMPERATURE: -30°C TO 70°C
3. STORAGE TEMPERATURE: -30°C TO 80°C
4. FPC BENDING RADIUS IS R1.0MM MIN
5. USB CONNECTOR IS MOLEX 53015-0410 OR EQUIVALENT
6. ALL ROHS ASSEMBLY
7. (\*) DIMENSION FOR REFERENCE



THIS DOCUMENT IS CONFIDENTIAL PROPRIETARY INFORMATION OF OCULAR CORPORATION AND SHALL NOT BE DISCLOSED OR COPIED OR USED FOR ANY PURPOSE OTHER THAN FOR WHICH IT IS SPECIFICALLY FURNISHED WITHOUT THE PRIOR WRITTEN CONSENT OF OCULAR CORPORATION.

UNLESS OTHERWISE NOTED:			
UNITS	DECIMAL	DRAWING TITLE : 7' No Cover Glass,mxT384E,USB	
MM	.XX ±0.2	DRAWING No. : F070-0384E-000	
ANGLES	±0.5°	REV:C	
THIRD ANGLE PROJECTION		SCALE 1 : 1	SHEET: 1 OF 1