



258.00 TOP GLASS
 228.80 BOTTOM GLASS
 223.78 VIEW AREA
 221.76 ACTIVE AREA
 18.00±0.10
 (120.00)
 (69.00)

12.20
 2.00
 15.20
 400.00 BOTTOM GLASS
 375.60 TOP GLASS
 371.60 VIEW AREA
 369.60 ACTIVE AREA
 (80.50)
 PT
 FPC-YL
 FPC-XB
 FPC-YR
 PT
 30.50±0.10
 (72.83)
 (120.00)
 18.00±0.10
 30.50±0.10
 (154.67)

2.60±0.50
 1.10 TOP GLASS (ITO FACE DOWN)
 0.40 OCA
 1.10 BOTTOM GLASS (ITO FACE UP)

2.40 MAX
 Components
 height
 1.60 PCB

4.80 MAX
 Components
 height
 1.60 PCB

(34.50)
 26.00
 20.50
 27.75
 28.50
 2.75
 4-φ2.50
 34.00
 (112.00)
 130.00
 124.50
 (64.00)
 2.75
 4-φ2.50
 84.50
 90.00
 2.75
 (40.00)

J3(USB) PIN TABLE

PIN#	J3 (USB)
1	5.0V
2	D-
3	D+
4	GND

- NOTES:
 1. ALL UNITS IN MM.
 2. OPERATING TEMPERATURE: -30°C TO 70°C
 3. STORAGE TEMPERATURE: -30°C TO 80°C
 4. FPC BENDING RADIUS IS R1.0MM MIN
 5. USB CONNECTOR IS MOLEX 53015-0410 OR EQUIVALENT
 6. ALL ROHS ASSEMBLY
 7. (*) DIMENSION FOR REFERENCE

<p>OCULAR. DISPLAY YOUR ADVANTAGE</p> <p>THIS DOCUMENT IS CONFIDENTIAL PROPRIETARY INFORMATION OF OCULAR CORPORATION AND SHALL NOT BE DISCLOSED OR COPIED OR USED FOR ANY PURPOSE OTHER THAN FOR WHICH IT IS SPECIFICALLY FURNISHED WITHOUT THE PRIOR WRITTEN CONSENT OF OCULAR CORPORATION.</p>	UNLESS OTHERWISE NOTED:		DRAWING TITLE : 17' ND Cover Glass,1716E,USB	
	UNITS	DECIMAL		
	MM	.XX ±0.2	DRAWING No. : F170-1716E-000	
	ANGLES	±0.5°	REV: B	
THIRD ANGLE PROJECTION			SCALE 1 : 1	SHEET: 1 OF 1